

MANUAL AND PNEUMATIC STRAPPING TOOLS FOR STEEL STRAP

EST 8527 - 8528



CHART OF TYPES

MODEL	ITEM.NO.	STRAP WIDTH
STPM 19	107.190.040	19 mm 3/4"
STPM 25	107.250.040	25 mm 1"
STPM 32	107.320.040	32 mm 1 1/4"

FLAT AND ROUND SURFACES MANUAL SEALER FOR STEEL STRAP WITH SEAL

TECHNICAL DATA

Strap quality	standard Rmax. 850N/mm
Joint type	seal - single notch
Seal type	overlap min. 45 mm length (1 - 3/4")
Package type	flat and round surfaces
Strap width	19-25-32 mm / 3/4" - 1" - 1 1/4"
Strap thickness	from 0.6 up to 0.8 mm / 0.024" - 0.031"
Weight	around 2,8 kgs / 6.1 lbs

STTMR 19-25-32



CHART OF TYPES

MODEL	ITEM.NO.	STRAP WIDTH
STTMR	108.990.040	19-32 mm 3/4" - 1 1/4"

FLAT AND ROUND SURFACES MANUAL TENSIONER FOR STEEL STRAP WITH SEAL

TECHNICAL DATA

Strap quality	standard & high tensile Rmax. 1100N/mm
Package type	flat and round surfaces
Strap width	19-25-32 mm / 3/4" - 1" - 1 1/4"
Strap thickness	from 0.6 up to 1 mm / 0.024" - 0.04"
Max tension / gear ratio	around 8500N - 1900 lbs / around 1:28
Weight	around 4,9 kgs / 10.8 lbs

STP 19-25-32



CHART OF TYPES

MODEL	ITEM.NO.	STRAP WIDTH
STP 19	103.190.050	19 mm 3/4"
STP 25	103.250.050	25 mm 1"
STP 32	103.320.050	32 mm 1 1/4"

FLAT AND ROUND SURFACES PNEUMATIC SEALER FOR STEEL STRAP WITH SEAL

TECHNICAL DATA

Strap quality	standard high tensile Rmax. 1100N/mm
Joint type	seal - single notch
Seal type	overlap min. 45 mm length (1 - 3/4")
Package type	flat and round surfaces
Strap width	19-25-32 mm / 3/4" - 1" - 1 1/4"
Strap thickness R850N/mm ²	from 0.6 up to 1.1 mm / 0.024" - 0.043"
Strap thickness R1100N/mm ²	from 0.63 up to 0.9 mm / 0.025" - 0.035"
Air pressure	from 5 upto 6.5 bar max / 72 - 92 psi
Air consumption	3 l/s - 6.4 cu ft / min
Weight	around 3,8 kgs / 8.3 lbs